
The #9710 Dust Eliminator is both a dust box and dust collection system for your #9565 Pro Stand! Operating as a dust box, it is very effective at containing dust/debris expelled from your router, and couple it with a dust collection system, it significantly increases the capture of dust/debris while reducing noise! The installation process takes approximately 20 minutes, as the design is meant for easy installation and removal!

- 1. Before you begin, verify that the lower stringers on your #9565 Pro Stand have the shelf ledge installed toward the floor. This is important, as the floor section of the Dust Eliminator will sit on that ledge and creates the bottom of the dust box!
- 4. We recommend that you install the dust port with the screw heads on the INSIDE of the dust box. This is the side that has the label "FLOOR" on it. This prevents dust/debris from gathering on them.



2. Remove your router or lift! Then loosen all of the #9565 Pro Stand corner bolts, there are four per corner. This will ease the installation of the Dust Eliminator bottom, sides and front.



5. The Dust Eliminator floor section exterior will look like this.
That way you can connect a 4" hose or fitting to it for dust extraction. Note: the nuts and washers are on this side!



 Before installing the Dust Eliminator floor section, you must attach the 4" dust port. Locate four (4) screws, washers and nuts. These are very small and will need a #1 Philips head screwdriver.




6. Install the Dust
Eliminator floor
section by tilting it
sidewaze and
inserting it between
the legs. Align the
back right rear
corner first, then the
front right corner and
slowly drop the floor
section into place.



NOTE: all sections are designed to be snug, GENTLY tamp them into place.

7. Install the Dust
Eliminator back
section (label facing
inward) by tilting it
sidewaze and
inserting it between
the legs. Align and
seat the top first, then
GENTLY press the
bottom of the section
into place.



10. Attach the doorknob to the access door on the Dust Eliminator Max View front panel.



8. Install the Dust Eliminator left side section (label facing inward) by tilting it sidewaze and inserting it between the legs. Align and seat the top first, then GENTLY press the bottom of the section into place.



11. Install the Dust
Eliminator Max View
front panel section
(hinges will be on the
left side, the door
opens outward) by
tilting it sidewaze and
inserting it between
the legs. Align and
seat the top first,
then



9. Install the Dust
Eliminator right side
section (label facing
inward) by tilting it
sidewaze and
inserting it between
the legs. Align and
seat the top first, then
GENTLY press the
bottom of the section
into place.



12. Once you have the top aligned, GENTLY press the sides and bottom of the Max View panel into place.



13. Ensure that all of the sections are properly in place and you are satisfied with the fitment. Next we finalize the stand.

## **MLCS Woodworking**

## Installing the #9710 Dust Eliminator

**For Customer Use Only** 

14. Using a bar clamp or whatever clamp you have, pull the cabinet square and retighten all of the corner bolts that were loosened in step #2.



15. Your Dust Eliminator is now ready to use!

9710 Dust Eliminator Parts List		
Part Number	Count	Description
9710-1	1	Floor Section Panel
9710-2	1	Rear Section Panel
9710-3	1	Left Section Panel
9710-4	1	Right Section Panel
9710-5	1	Max View Front Section Panel
9710-6	1	Max View Easy Access Doorknob Set – (1) Doorknob (1) Washer (1) Nut
9710-7	1	Floor Section Dust Port Fitting
9710-8	1	Floor Section Dust Port Screw Set – (4) Screws (8) Washers (4) Nuts